

OCBS-D8000 PDA
 5.1
 2G 16G ROM TF 32 GB;
 ARM Cortex-A53 64 1.3GHz;
 4G LTE 3G WCDMA;
 GPS A-GPS;
 800 LED;
 SIM PSAM SD TF;
 3.7V 400mAh;
 4.0 QVGA;
 IP65;
 6 1.5

Display	1.52" (40mm) x 77mm x 29mm W
Weight	<500g
Camera	4.0 QVGA TFT-LCD (65mm) 480x800 QVGA LED
Storage	SIM PSAM SD TF
Connectivity	USB 2.0 RS-232
Battery	3.7V 400mAh
Power	8W
Processor	ARM Cortex-A53 64 1.3GHz
Memory	2G
ROM	16G NAND Micro SD / TF 32G
Standards	IEEE 802.11b / g
FDD-LTE	1920MHz-1980MHz; 2110MHz-2170MHz 1710MHz-1785MHz; 1805MHz-1880MHz 2496MHz-2690MHz; 2496MHz-2690MHz
WCDMA / GSM	WCDMA 1850MHz-1910MHz; 1930MHz-1990MHz 880MHz-915MHz; 925MHz-960MHz GSM 850MHz; 824MHz-849MHz; 869MHz-894MHz 900MHz; 880MHz-915MHz; 925MHz-960MHz 1800MHz; 1710MHz-1785MHz; 1805MHz-1880MHz 1900MHz; 1850MHz-1910MHz; 1930MHz-1990MHz
Input	2.0 + EDR 5-10
Temperature	-20°C to 50°C
Humidity	5% RH - 95% RH
Shock	1000g / 0.5ms 6
IP Rating	IP65
OS	Android 5.1
SDK	JAVA
Barcode	SE655 5 MIL 0ft.candles-1000ft.candles 50 / 53±3°
Barcode	UPC / EAN Bookland 128 39 93 11 5 2 5 2 2 2 2 5 0 1 0 GS1 DataBar
Barcode	Mingde 966 955 Honeywell N4313 4 MIL 1000ft.candles 10764 104 ±12 / Bothway 47 ±35° / 35 ±3°
Barcode	UPC / EAN 128 39 CODE 93 Code 11 5 2 5 2 2 2 2 2 2 5 0 1 0 RSS
CMOS	3096 N3680
Barcode	752 x 480 900ft.candles / 96900
Barcode	65nm ± 10nm
Barcode	PDF417 MicroPDF417 RSS TLC-39 QR QR MAXICODE POSTNET Japan Postal KIX3
RFID	LF ISO11784 / ISO11785 HF 13.56MHz; ISO14443A / B 800 LED A-GPS

XXXXXXXXXX

