

OCBS 00000000

OCBS -L009

OCBS



ñ 200scan / sec h

ñ

ñ KBW RS232 USB;

ñ

ñ

OCBS

OCBS	
OCBS	650nm
OCBS	200
OCBS	32
OCBS	2.5~600mm 100 UPC / EAN
OCBS	50mm @ 60mm 220mm @ 200mm
OCBS	
OCBS	
OCBS	3mil / 5mil
OCBS	30
OCBS	UPC / EAN UPC / EAN UCC / EAN 128 Code 39 Code 39 ASCII Trioptic Code 39 Code 128 Code 128 Full ASCII Coda bar Interleaved 2 of 5 Discrete 2 of 5 Code 93 MSI Code 11 RSS 2 of 5 MSI / Plessey / UCC / EAN 128 GS1 RSS
OCBS	±65°; ±60°; ±42°
OCBS	

□□□□□□	PS2□RS232□USB
□□□	5V DC±5□
□□□	85 mA□□□□; 100□□□□
□□□	□□□□LED
□□	ABS + PC
□□	□□□
□□□□□	156 * 68 * 83 mm□□*□*□□
□□□	235□
□□□	□□□□□
□□□□	
□□□□□	0 □□C~45°C
□□□□□	-40 □□C~60 □□C
□□□	5□-90□□□□□□
□□□□□	□□+/- 15KV□□□□□□+/- 8KV□□□□
□□□□	0~100,000 LUX
□□□□□	□□□□□□1.5□□□□□□□□□□
□□□□	EN60825-1□1□