

___OCBS -L009



- \tilde{n} 200scan / sec h____;
- ñ [][][];
- $\tilde{n} \ \, \square \square \mathsf{KBW} \square \mathsf{RS232} \square \mathsf{USB};$
- $\tilde{n} \ \square ;$
- \tilde{n} 00000 00000;

0000	
	650nm□□
	32[
	2.5~600mm[]100[]UPC / EAN[]
	50mm @ 60mm[]220mm @ 200mm
	3mil/ 5mil
	30000000
	UPC / EAN UPC / EAN UPC / EAN UPC / EAN 128 Code 39 Code 39 ASCII Trioptic Code 39 Code 128 Code 128 Full ASCII Coda bar Interleaved 2 of 5 Discrete 2 of 5 Code 93 MSI Code 11 RSS 0 5 MSI / Plessey 0 5 MSI / Plessey 0 5 MSI / EAN 128 0 GS1 0 GS1 0 CSS
	±65°0000; ±60°0000; ±42°000
0000	

PS2[]RS232[]USB
5V DC±5[]
85 mA; 100
ABS + PC
156 * 68 * 83 mm[[]*[]*[]
235[]
0 □□C~45°C
-40 □□C~60 □□C
50-9000000
00+/- 15KV00000+/- 8KV0000
0~100,000 LUX
EN60825-1[]1[]