

OCBS-LA01

ModelNo OCBS-LA01

Spec

- Wavelength: 650-670nm
- Power: 100mW SPS
- Beam Diameter: 8mm
- Range: 1 / 3,000,000
- Spot Size: 2.5~600mm
- Resolution: 0.1mm @ 4mm PCS 0.9
- Accuracy: 20um @ 650nm
- Angle: 45° / 60°
- Barcode: UPC / EAN / UCC / EAN128 / 39 ASCII / 39 trioptic / 128 / 128 ASCII / codabar / 2 of 5 / 5 of 93 / MSI / 11 / ATA / RSS / 2 of 5 ...
- Interface: PS2 / RS232 / USB
- Voltage: DC + 5V +/- 5%
- Current: 100 mA; 110mA
- Power Consumption: < 30mA
- Protocol: RS232
- Dimensions: L200mm x W72mm x H58.5mm
- Weight: 480g
- Material: Aluminum
- Color: Silver

Table

OCBS-LA01	
Wavelength	650-670nm
Power	100mW SPS
Beam Diameter	8mm
Range	1 / 3,000,000
Spot Size	2.5~600mm
Resolution	0.1mm @ 4mm PCS 0.9
Accuracy	20um @ 650nm
Angle	45° / 60°
Barcode	UPC / EAN / UCC / EAN128 / 39 ASCII / 39 trioptic / 128 / 128 ASCII / codabar / 2 of 5 / 5 of 93 / MSI / 11 / ATA / RSS / 2 of 5 ...
Interface	
Interface	PS2 / RS232 / USB
Voltage	DC + 5V +/- 5%
Current	100 mA; 110mA
Power Consumption	< 30mA
Protocol	RS232
Dimensions	L200mm x W72mm x H58.5mm
Weight	480g
Material	Aluminum
Color	Silver





OCBS-LA01



[www.ocominc.com](http://www.ocominc.com)

