

OCBS-LA01

OCBS-LA01

Option

- ñ RS232; RS485;
- ñ RS485;
- ñ RS485;
- ñ KBW RS232 USB;
- ñ RS485;

General

Wavelength

650-670nm

Power

100mW SPS

Channels

8

Capacity

1 / 3,000,000

Dimensions

2.5~600mm

Resolution

0.10nm

Aperture

4mm PCS 0.9

Wavelength Accuracy

20nm @ 650nm

Viewing Angle

45° 60°

Barcode

UPC / EAN UCC / EAN128 39 39 ASCII 39 trioptic 128

Barcode

128 ASCII codabar 2 of 5 2 of 5 93 MSI 11 ATA RSS 2 of 5

Barcode

...

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Barcode

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

Power

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

EMI / RFI

PS2 RS232 USB

DC + 5V +/- 5%

100 mA; 110mA

< 30mA

RS232

L200mm x W72mm x H58.5mm

480

pos pos

±15KV ±8KV

1.5

FCC B CE

2 IEC60825-1 EN60825-1



OCBS-LA01



[www.ocominc.com](http://www.ocominc.com)

