

OCBS-LA01

OCBS-LA01

Option

- ñ RS232C; RS485;
- ñ RS232C; RS485;
- ñ RS232C; RS485;
- ñ KBW; RS232C; USB;
- ñ RS232C; RS485;

General

Model

Wavelength	650-670nm
Power	100mW SPS
Channels	8
Resolution	1 / 3,000,000
Spot Size	2.5~600mm
Beam Diameter	10
Beam Quality	0.10 @ 4mm M ² PCS 0.9
Wavelength Accuracy	20nm @ 650nm
Beam Angle	45° ~ 60°
Barcode	UPC / EAN / UCC / EAN128 / 39 / ASCII / trioptic / 128 / 128 / ASCII / codabar / 2 of 5 / 2 of 5 / 93 / MSI / 11 / ATA / RSS / 2 of 5
...	...

Power

Power Source	PS2; RS232C; USB
Voltage	DC + 5V +/- 5%
Current	100 mA; 110mA
Power Consumption	< 30mA
Power Regulation	RS232C
Dimensions	L200mm x W72mm x H58.5mm
Weight	480g
Material	Aluminum
Finish	Black

Environment

Operating Temperature	0~40°C
Storage Temperature	-30~60°C
Humidity	5~95% RH
Vibration	pos / pos
Shock	±15KV / ±8KV
Drop	1.5m

Compliance

EMI / RFI	FCC B / CE
Safety	2 / IEC60825-1 / EN60825-1



OCBS-LA01



www.ocominc.com

