

OCBS -LA06

OCBS-LA06



Features

- Handheld
- Handheld
- Handheld
- Handheld
- KBW RS232 USB
- Handheld

Specifications

Wavelength	650-670nm
Beam diameter	200mm
Range	2.5~600mm 100 UPC / EAN
Resolution	mm
PCS	0.9 0.10mm 4mil
Barcode types	20 barcode types @ 650nm
Barcode types	UPC / EAN 128 39 39 ASCII 39 trioptic 128 128 ASCII codabar 2 of 5 2 of 5 93 MSI 11 ATA RSS 2 of 5 ...
Interface	PS2 RS232 USB
Voltage	DC + 5V +/- 5
Current	100mA
Power consumption	< 40mA

型番	RS232型
傾斜角	45°~60°
外形寸法	L165.42mm X W69.72mm X H89.67mm
重量	140g
材質	樹脂
色	黒色
使用温度範囲	0℃~50℃
保存温度範囲	-40℃~70℃
湿度範囲	5~95%RH
耐電圧	+/- 15KV
耐電流	+/- 8KV
耐電圧時間	1.5分
規格	
EMI / RFI	FCC A CE
認証	CDRH 2



OCBS-LA06





OCBS-LA06





000000t / twestern uion00paypal000000000000000000000000aliexpress000000
 00http://www.aliexpress.com/store/40344800tracelog = minisite CI0

3.00

```
OCOM[0][0][0][0][0][0][0][0][0][0][0][0][0][0][0][0][0][0];
```

□□□□□□500□□□□□□□□□□□□□□□□100□□□□□□□□□□□□

```
000000000000000012 + 1000000000000000024000000;
```

0000300000000000DOA DOA0000000000000000

[illegible]

4.□□□□

000000000000T / T LC Western Union Escrow 00000000000000000000T / T Western Union Escrow Paypal
 000000.Escrow 000Alipay.com 00000000000000000000Moneybookers Visa MasterCard 00000000000000000000
 00Maestro 00Solo 00Carte Bleue 00Pos tePay 00CartaSi 004B 00Euro6000

5.00

□ □

6.11

European...

□□□□□□133□□□□1300□□□□□□□□□□□□□□□□02□□□□□500□□□.....□□50□□□□□□□□□□

Page 10

OCOM

□□□500□□□□□□□□POS□□□□□□□□□□

02 Star

1500□□□□□133□□□;

9 OEM / ODM

POS□□□□□□□□□□□□□□□□

□□□□□□□□

FCC CE Soncap POA BIS

 $12 + 1\boxed{}$

□□ "□□□□□□"

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □