

RS232 / USB

OCBS -T2001

1. 1D / 2D

1. 1D / 2D
2. 1D / 2D
3. 1D / 2D
4. Windows / Android / Linux

2. 1D / 2D

1D / 2D		
1D		640x480 CMOS
1D / 2D	1D	128 UCC / EAN-128 128 EAN-8 EAN-13 ISSN 1D UPC-E UPC-A Interleaved 2 of 5 ITF-6 ITF-14 25 25 25 39
	2D	PDF417 QR DATAMATRIX
1D / 2D		≥5mil
1D / 2D		QR 30MIL 0-15CM 128 10MIL 0-12CM
1D / 2D		±60°@ 0°Roll 0°Skew 360°@ 0° 0° ±55°@ 0° 0°
1D / 2D		≥30
1D / 2D		RS-232 USB
LED		
3. 1D / 2D		
1D / 2D		IP5X
1D / 2D		-20°C 50°C
1D / 2D		-40°C 70°C
1D / 2D		5 95
4. 1D / 2D		
1D / 2D		USB 228g RS232 261g
1D / 2D		102 * 82 * 73 L * W * H
5. 1D / 2D		
1D / 2D		5V + 0.25V
1D / 2D		430
1D / 2D		<200; 150 ±15; 80 ±2





OCBS-T2001





OCBS-T2001









OCBS-T2001





Reliable One-Stop Supplier for POS and Auto-ID Related Products

5.

