

pdf417 (OCBS-T201)

○○○○○○○○○○
 ○○○○○○○○○○
 ○○○○○○○○
 ○○○○○○○○
 ○○○○○○○○○○○○

| | |
|--------------------------|--|
| Performance parameters | |
| Light source | White LED |
| Buzzer | Seven tones or silent |
| Lamp | White |
| System interface | KBW, RS232,USB |
| Physical parameters | |
| Volume(Lx W x H) | Product size 78 mm x 75 mm x 141mm (3.2" x 3.3" x 5.9"), |
| Weight | Product size180 g (12 oz) |
| Electrical parameters | |
| Input voltage | 5.5 VDC ± 0.25 V |
| Work power | 2.0 W (430 mA @ 5 V) |
| Standby power | 0.5 W (100 mA @ 5 V) |
| Environmental parameter | |
| Operating temperature | 0° C - 40° C |
| Storage Temperature | -40°C -60°C |
| Humidity | 0% to 95% relative humidity (no condensation) |
| Antiknock characteristic | Withstand 1.5 meters high drop from concrete floor. |
| Dust-proof | Seal to prevent air dust particle erosion. |
| Scanning parameters | |
| Scanning mode | Omni directional (640X480) |
| Highest Reflectivity | Max 20% reflectivity can be read |
| Scanning Angle | 70°, 75° |

