

OCBS-T203 3 USB

M / N OCBs-T203

1D / 2D

Aisino

Aisino

32 DSP	32 ARM DSP 1D
	2D
	UPC / EAN 100 PCS90
	5mil
	USB windows
	LED operation.standby

重量	50kg
----	------

规格

封装	CMOS
尺寸	752 * 480 CMOS
特性	LED
接口	Code128, UCC / EAN-128, AIM-128, EAN-8, EAN-13, ISBN / ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2, Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, GS1-DataBar, RSS, RSS-14, RSS, PDF417, QR, QR1 / 2, Micro, ECC200, ECC000, 050, 080, 100, 140
厚度	≥5mil
间距	2.5mm
温度范围	±50°@ 0°
湿度范围	±360°@ 0°
其他	±60°@ 0°
接口	USB HID-KBW, USB HID-POSTTL-232, RS-232
角度	44°/33.2°
封装	EAN-13: 0-20mil, PDF 417: 0-7mil, Code 39: 0cm-12cm, 5mil, 10MIL, 10-15mil
尺寸 L * W * H	89 * 108 * 143mm
重量	245g
温度范围	20°C + 50°C, -4°F + 122°F, -40°C + 80°C, -40°F + 176°F
ESD	ESD
电压	±14kV, ±8kV
1.2	
IP 52	





