## OCBS-T203

′ 2Daaaaaaaaaaaaa aaaaaaaaaaaaaaaaaaaaaa

## 

32[] [][][] [][DSP [][]	32_ARMDSP1D1D
	002D 000000000
	□UPC / EAN 100□□PCS90□□
0 00	
000 00	
USB	
000 00	
000 00000	
000 000	
00 0000	
0000	0000 007200000000000 000
000 00	
000 00000	
00LED 0000	
0000 00	
00 000	0 000000000000050kg 00000000000000000000

## 

		CMOS			
		752 * 480 CMOS			
		Code128@UCC / EAN-128@AIM-128@ EAN-8@EAN-13@ISBN / ISSN@UPC-E@			
		UPC-A Interleaved 2 of 5 ITF-6 ITF-14 5 Matrix 2 Industrial			
		25  Standard 25  Code 39  Codabar  Code 93   Code 11  Plessey  MSI-			
		Plessey[]GS1-DataBar[]RSS[][][]RSS-14[]RSS-[][][]RSS-[][]			
		PDF417[]QR[][]QR1 / 2[]Micro[][][] [][]ECC200[]			
		ECC000,050,080,100,140			
		≥5mil			
		2.5[]/[]			
		±50°@ 0°[][][0°][]			
		±360°@ 0°0°			
		±60°@ 0°[][[]0°[]			
		USB HID-KBW□USB□□□□□USB HID-POSTTL-232□RS-232			
		□□44°□□□33.2°			
	EAN-13	02013mil_			
	PDF 417	076.67mil_			
	<u>□</u> □39	0cm-12cm[5mil[][][]			
		000-40010MIL0			
		000-100015000			
□□□L * W * H□		89 * 108 * 143mm[[]2[]			
		245			
20°C+ !					
4°F_122°F_					
-40°C∏+ 80°C		□-40°F□176°F□ □□			
5_95		ESD			
±140000		0000±8 kV00000 00			
1.2					
IP 52					

ı	×
I	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ł	
ı	
ı	
ı	
ı	
ı	
1	

1	