

OCBS -T204

M / N

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204

OCBS -T204		CMOS
OCBS -T204		752 * 480 CMOS
OCBS -T204		OCBS -T204 LED
OCBS -T204		Code128 / UCC / EAN-128 / AIM-128 / EAN-8 / EAN-13 / ISBN / ISSN / UPC-E / UPC-A / 5 / 2 / ITF-6 / ITF-14 / 2 / 5 / 25 / 39 / Codabar / 93 / 11 / Plessey / MSI-Plessey / GS1-DataBar / RSS / RSS-14 / RSS- Limited / RSS-Expand / PDF417 / QR / QR1 / 2 / Micro
OCBS -T204		≥400
OCBS -T204		2.5 m /
OCBS -T204	OCBS -T204	±50°@ 0°0°
	OCBS -T204	±360°@ 0°0°
	OCBS -T204	±60°@ 0°0°
OCBS -T204		USB HID-KBW / USB
OCBS -T204		44°33.2°
OCBS -T204	EAN-13	0cm—20cm13mil
	PDF 417	0cm-7cm667
	39	0cm-12cm5mil1
	OCBS -T204	0cm-4cm10
	OCBS -T204	0cm-10cm15
OCBS -T204		20°C+ 50°C-4°F122°F
OCBS -T204		-40°C+ 80°C-40°F176°F
OCBS -T204		595
OCBS -T204		±14 kV±8 kV
OCBS -T204		OCBS -T2041.2m
OCBS -T204		IP 52











OCBS-T204

