

m / nOCBS -t207

OCBS	OCBS -T207
IP	IP52
ABS	ABS + PC
MCU	32ARM MCU
USB	USB
LED	LED
DC	DC 5V±5%
Current	200mA; 231mA; 290mA
Power	1.0W; 1.16W; 1.45W
OS	Linux; Android; Windows XP; 7; 8; 10; MAC
Voltage	15kv air
Memory	1.2M
CMOS	CMOS
Speed	25cm / sec; 10mil QR
Roll	ROLL360°; 45°; YEW60°
Angle	32°* 30°
Distance	≥30
Lux	0~10000Lux
Frequency	1/500
Resolution	
Encoding	code39 4mil.
Barcode	code39 4.17mil.~15mil. 7 - 13 code39 10.83mil.~16mil. 8 - 15cm. code39 10.83mil.~8mil. 6cm - 11cm. QR 10.83MIL.~8mil. 5 - 13
Barcode	1D; EAN-8; CODE 39; EAN-13; UPC-E; 93; UPC-E1; UPC-A; Plessey; 2/5; 25; 25; Codabar; MSI-Plessey; UPCE0 / E1; GS1-128; GS1 DataBar; 2; itf-14; Code32; 11; ISBN; ISSN; 25,2D; Data Matrix; QR; PDF417

□□□□	
□□	□□□200g
□□	190 * 180 * 123mm
20□1□□	645 * 390 * 400mm / 11.3kg
□□	
□□□□□□	0□45□□□□10□□80□□□□
□□□□□□	-20□60□□□□10□□90□□□□





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207

