

2D

M / N OCBS -T209

300,000

4mils

LED

1D 2D

Microsoft Windows / Linux / Android / IOS / MacOS

| | |
|------|---|
| | OCBS -T209. |
| | |
| | RS-232; USB HID; USB COM; HID POS |
| | 1.8M. |
| | LED / |
| | 5 VDC +/- 10% / 500mA |
| | < 300 mA Standby current < 210 mA |
| | Microsoft Windows / Linux / Android / IOS / MacOS |
| ESD | 8 kv. |
| | 1.2m / 4.0 |
| | |
| | 640 * 480 |
| | LED LED |
| | 2M / |
| | 120fps / s. |
| | 0-360°; ±60°; ±60° |
| | ≥15 |
| | 0 -100,000 |
| | 0.102mm / 4mils. |
| | <p>5mil 128 0mm-70mm 5mil ean-13 0mm-70mm. 4mil ean-13 0mm-240mm. 5mil pdf417 0mm-60mm. 10mil. PDF417 0mm-170mm. 15mil. PDF417 0mm-270mm. 20mil DM. 0mm-80mm.</p> |
| | <p>1D 1D GS1 DataBar™ 2D AZTEC; maxicode; MicroQR GS1 Databar; GS1 Databar; GS1 DataBar; GS1 DataBar COM pos ITE; micropdf417; PDF417</p> |
| | |
| | 450.G |
| | 190 * 105.* 108. |
| 20 1 | 560.*225.* 400mm / 10.0 |

| | |
|--------|-----------------------|
| □□ | |
| □□□□□□ | 0□45□□□□10□□80□□□□□ |
| □□□□□□ | -20□60□□□□10□□90□□□□□ |

□□□□











