



- T209)

特性

1. 高解像度
2. 30fps
3. 4mil
4. LED
5. &
- 6.
- 7.
8. Windows/linux/Android/IOS/MacOS

仕様

型番	OCBS-T20 9
インターフェース	RS-232C USB 無線 USB
伝送速度	1.8M
照明	LED/可変輝度
消費電力	5 W (± 10%)/500 mA
動作電圧	動作電圧 < 300 mA 動作電圧 < 210 mA
動作OS	Windows/Linux/Android/IOS/MacOS
ESD耐性	8kV
設置高さ	設置高さ 1.2m/4.0ft 可変
撮像素子	S CMOS
照明	O LED CMOS
解像度	LED 可変 LED
撮像素子	2M
撮像素子	120°/°
撮像素子	0-360° ±60° ±60°
撮像素子	≥15%
撮像素子	0 -100,000
撮像素子	0.102 4
撮像素子	5mil CODE128 0mm—70mm 500 EAN-13 0mm—70mm 400 EAN-13 0mm—240mm 500 PDF417 0mm—60mm 1000 PDF417 0mm—170mm 1500 PDF417 0mm—270mm 2000 0mm—80mm GS1 DataBar™ 2D GS1 DataBar Expanded Stacked GS1 DataBar GS1 DataBar GS1 PDF417 PDF417
撮像素子	GS1 DataBar™
撮像素子	GS1 DataBar Expanded Stacked GS1 DataBar GS1 DataBar GS1 PDF417 PDF417
重量	重量 450 g
寸法	190*105*108 mm
2011	560 * 225 *400mm/1.0
動作温度	0~45℃ ±10%~80%
動作湿度	-20 ~ 60 ±10%~90%











