



- T209 )

特性

1. 高解像度
2. 30fps
3. 4mil
4. LED
5. &
- 6.
- 7.
8. Windows/linux/Android/IOS/MacOS

仕様

型番	OCBS-T20 9
インターフェース	RS-232C / USB / 無線 USB
伝送速度	1.8M
照明	LED/可変輝度
消費電力	5 W (± 10%) / 500 mA
動作電圧	動作電圧 < 300 mA 動作電圧 < 210 mA
動作OS	Windows/Linux/Android/IOS/MacOS
ESD耐性	8kV
設置高さ	1.2m/4.0ft 可変
撮像素子	S CMOS
照明	O LED / CMOS
解像度	LED / CMOS
視野角	2M / 120°
照射距離	0-360° ±60° ±60°
照度	≥15%
検出範囲	0 -100,000
検出精度	0.102 / 4
検出方式	5mil CODE128 0mm—70mm 500 EAN-13 0mm—70mm 400 EAN-13 0mm—240mm 500 PDF417 0mm—60mm 1000 PDF417 0mm—170mm 1500 PDF417 0mm—270mm 2000 0mm—80mm
検出機能	GS1 DataBar™ 2D GS1 DataBar Expanded Stacked / GS1 DataBar / GS1 DataBar / GS1 / PDF417 / PDF417
重量	450 g
寸法	190*105*108 mm
2011	560 * 225 * 400mm / 1.0
動作温度	0~45℃ ±10%~80%
動作湿度	-20 ~ 60 ±10%~90%











