

2D

m / n OCBS -t211

1280 * 1024

2D

1.5 IP52

	OCBS -T211
	2D
	ABS + PC.
IP	IP52.
	USB RS232
	32 ARM MCU + DSP
	LED
	; 1D 1D 2D
	DC 5V 2A
	1.71W; 0.87W; 2.45W
	Linux Android Windows XP 7,8,10 Mac
ESD	15kV
	1.5M
	CMOS 1280 * 1024
	LED
	3.82
	1/5000000

□□□□	ROLL360°□□□45°□YEW45°
□□□□□	≥30□
□□	code39 4mil.
□□□□	5MIL CODE39□1 cm - 14□□□13mil UPC-A□2□□ - 34□□ 20mil Code39□1 cm - 35□□□6.7mil PDF417□1□□ - 9□□ 10mil□□□□□1□□ - 10□□ 15mil□□□□□1□□ - 20□□ 1D□□□0□□ - 50□□□2D□□□0□□ - 50□□
□□□□	1d□□□2□□5□□□□2□□5□□matri 2□5 code39-range□code39-full ascii□code32 Code93-Regular□Code93-Full ASCII□Code128 EAN / GSL / UCC-128□Codabar□MSI EAN / JAN-13□UPC-A□EAN / JAN-8 □□11□UPC-E0 / E1 2D□Micro QR□□□□□□QR Aztec□PDF417
□□□	
□□	□□□1000g.
□□	200 * 183 * 154□□
12□1□□	615 * 385 * 325mm / 13.2kg
□□	
□□□□□□□	0□45□□□□10□□80□□□□□
□□□□□□□	-20□60□□□□10□□90□□□□□



OCBS-T211





OCBS-T211





OCBS-T211





OCBS-T211



