

OCBS-T214

# OCBS-T214

OCBS

OCBS  
OCBS/OCBS  
OCBS  
OCBS

OCBS

OCBS-T2 14	OCBS-T2 14
USB	USB
5V	5V
380	380
24 0	24 0
190	190
8 G r.m.s. 10 500 Hz 2 3	8 G r.m.s. 10 500 Hz 2 3
CMOS	CMOS
LED	LED
44 ° ( ), 34 °	44 ° ( ), 34 °
> 0.4m/S	> 0.4m/S
±6 5 ° @ 0°Roll 0° Skew 360° @ 0° 0° ± 6 5 ° @ 0°Roll 0° Pitch	±6 5 ° @ 0°Roll 0° Skew 360° @ 0° 0° ± 6 5 ° @ 0°Roll 0° Pitch
20%	20%
0-100,000	0-100,000
Code39(5mil):0-120mm, Code39(13mil):0mm-240mm QR(20mil):0mm-210mm (QR 30*30mm):40mm-650mm (QR 23mm*23mm):20mm-550mm	Code39(5mil):0-120mm, Code39(13mil):0mm-240mm QR(20mil):0mm-210mm (QR 30*30mm):40mm-650mm (QR 23mm*23mm):20mm-550mm
Code128 / 128, EAN .UCC 2 of 5 ,RSS,Postnet,Plessey 39 , 93 , 11 , Standard 2 of 5UPC/EAN 2DPDF417Matrix 2 of 5MicroPDF417MaxiCode CodablockAztecTLC 39DataMatrix	Code128 / 128, EAN .UCC 2 of 5 ,RSS,Postnet,Plessey 39 , 93 , 11 , Standard 2 of 5UPC/EAN 2DPDF417Matrix 2 of 5MicroPDF417MaxiCode CodablockAztecTLC 39DataMatrix
437 g	437 g
151 *1 42 * 84 mm	151 *1 42 * 84 mm
45 10%~80%	45 10%~80%
-20 60 10%~90%	-20 60 10%~90%













