

OCBS 2D

OCBS -t214



OCBS

OCBS

OCBS 1D / 2D

OCBS

OCBS

OCBS

OCBS	
OCBS	OCBS -T214
OCBS	USB
OCBS	5V.
OCBS	380mA.
OCBS	240mA.
OCBS	190mA.
OCBS	8g r.m.s. 10 500 Hz 2 3

□□	
□□□	□□EX AAA1 URE CMOS□□□
□□	□□□□□LED
□□	44°□h□□34°□v□
□□□□	> 0.4m / s
□□□□	□□±65°@ 0°□□0°□□ 360°@ 0°□□□0°□□ □□±65°@ 0°□□0°□□
□□□□□	20□□□□□□□□
□□□□□	0-100,000□□□
□□	Code39□5MIL□□0mm-120mm□Code39 □13mil□□0mm-240mm QR□20mil□□0mm-210mm □□□□QR 3 * 3cm□□40mm-650mm □□□□□QR 2.3 * 2.3cm□□20mm-550mm
□□□□	1D□Code128 / EAN128□EAN.CCCOM pos ITE□ Interleaved2of 5□RSS□Pos TNET□Plessey□□□□ □39□Codabar□□□93□ □□11□Telepen□MSICODE□□□2□5□UPC / EAN□ 2D□PDF417□QR□□5□5□MicroPDF417□□□□□Pos T□□□□□Pos T□□□□Pos T□Maxicode□Codablock□Aztec□Dutch Pos T□TLC 39□Datamatrix□
□□□□	
□□	□□□437g
□□	151 * 142 * 84mm
□□	
□□□□□□□	0□45□□□□10□□80□□□□□
□□□□□□□	-20□60□□□□10□□90□□□□□











