

usb 1d&2d

(M/N:OCBS-T215)



□□

□□	
□□	OCBS-T215
□□	USB
□□□□	5V
□□□□	420□□
□□□□	400□□
□□□□	270□□
□□	
□□□	□□□□640*480 CMOS□□□
□□	□□ LED
□□	57.2°□□□□□44.2°□□□□
□□□□	> 0.3m/s
□□□□	□□ ±70°@ 0°Roll □ 0° Skew □□ 360°@ 0°Pitch □ 0° Skew □□ ±70°@ 0°Roll □ 0° Pitch
□□□□	20% □□□□□
□□□□□	0-100,000 □□□
□□□□	Code39(5mil):20mm-80mm, EAN13(13mil):10mm-160mm QR(15mil):10mm-140mm □□□□□15mil□□10mm-100mm PDF417 (10mil):10mm-120mm
□□□□	(Codabar),(Code 39),(Code 32),(Industrial 2 of 5),(Interleaved 2 of 5),(Standard 2 of 5),(Matrix 2 of 5),(Code 93),(Code 11),(□□ 128),(UPC-A),(UPC-E),(EAN/JAN-8),(EAN/JAN-13),(GS1 □□□(RSS14) (PDF417),(QR□),(Micro QR),(Data Matrix),(Aztec),(Hanxi□)
□□□□	
□□	□□□640g
□□	230*170*95mm
□□	
□□□□□□□□	0□45□□□□10%~80%□□□
□□□□□□□□	-20 □ 60 □□□□10%~90% □□□















Model: OCBS-T215

Interface: USB



OCBST2152214100001

Made in China





1. Introduction	1
2. Safety Precautions	2
3. Operation	3
4. Troubleshooting	4
5. Appendix	5

Special Precautions Manual

1. The device and also on the charging socket
operation when the work of the device. When charging
operation or please make sure for safety usage, and
the flow chart.

2. The device shall not be exposed with a flame, with smoke,
and a small amount of gasoline can be added to the device,
and then repair with a professional repair.

3. Special Precautions: This instruction has been strictly and
carefully checked and confirmed, but it still does not
exclude the occurrence and error or spilling lead
technology used, minimum good device will be connected in
the user manual of the instruction without remove the
copyright of this technology is subject to the company, and
no other work or technology may modify it.

**THE POWER CORD IS A POWER
CABLE, NOT A DATA CABLE.**



Copyright © 2010 by ocom. All rights reserved. This document is the property of ocom. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without permission in writing from ocom. The information in this document is subject to change without notice. ocom reserves the right to modify the contents of this document at any time without notice, and is not responsible for errors or for any consequences arising from the use of the information contained herein.





2D Barcode Scanner
Model: OCBS-T215 Color: Black
Interface: USB CE FC
Power Input: 5V1A
OCBS T215 2214100001
Made in China