

OCBS-T2 18

- 218)

1. 400

1. 400
2. 400
3. 640 * 480
4. 400

2. 400

	OCBS-T2 18
	USB
	5V
	315
	320 235m
	120
	CMOS 640*480
	(Aimer) LED, (Illumination) LED
	39 ° (x)29 °
	>= 4mil
	±6 5 ° @ 0°Roll 0° Skew 360° @ 0° 0° ± 6 5° @ 0°Roll 0° Pitch
	20%
	0-100,000
	39(5mil):0-70mm,Code39(13mil):0mm-170mm QR(20mil):0mm-110mm,QR(QR 30mm*30mm):0mm-300mm
	39 , 32 (PARAF) , Interleaved 2 of 5,NEC 2 of 5,Code 93,StraiGht 2 of 5 Industrial,Straight 2 of 5 IATA,Matrix 2 of 5,Code 11,Code 128,GS1-128,UPC-A,UPC-E, EAN/JAN-8,EAN/JAN-13,MSI,GS1 DataBar Omnidirectional,GS1 DataBar Limited,GS1 DataBar Expanded,(2 of 5), T Code , A ,-F, PDF417 , MicroPDF417 , GS1 C , ,Data Matrix,MaxiCode,Aztec, Codabar,Code39,Interleaved2of5,NEC2of5,Code93,Code128,GS1-128,UPC-A,UPC-E0,EAN/JAN-13,EAN/JAN-8,GS1-DataBar,PDF417,QR,DM,Aztec
	:249 g
	140.2* 84* 90.1 mm
	122X165X105mm /343g
301	525X430X360mm,11.8kg
	04510%~80%
	-20 60 10%~90%











