

\square M/N \square OCBS-T219 \square



	OCBS-T219
	ABSTPU
	USB
	□□5V±5%
	180mA 120mA
	Linux[][][]Windows XP[]7[]8[]10[]MAC
3000	IP52
3000	00000 1.2m 00000000
][]	
300	CMOS 640*480[][][][]
JD	(DD)DDLED
3000	
	□[39 ≥4[]
	□□ ±65°@ 0° □□□ 0° □□ □□ ±65°@ 0° □□□ 0° □□
	≥20%
	1/5000000
J0000	0-100,000 🖂
0000	1083m 2cm - 9cm 2083m 2cm - 21cm 39 5.83mil 1cm - 12cm 39 10.83mil 1cm - 21cm EAN13 9.17 1 - 15 EAN13 10.83 2 - 21 0cm - 43cm
0000	1D 2 of 5 TF-6 TF-14 SB-128 Code 11 UCC/EAN-128 GS1 Databar 2 of 5 Matrix2 of 5 Code 32 Code 128 EAN-13 EAN-8 Code39 UPC-A Codabar Standard 2 of 5 Plessey MSI-Plessey UPC-E Code 93 GS1 2D PDF417 DataMatrix QRCode Micro DF417 AZTEC Maxicode Micro QR
][]	280g±3g[][][][]
	106.2*105.0*155.3mm
	183*178*110□□/520□
20 🛮 1 🖺	615*420*390mm/10.4kg
00	
]]]][]&[]]	0□45°C□10%□80% □□□
	-20_6010%~90%













