

OCBS -W013

OCBS-W013

□□□

200MM / 10-60cm

70 2.4G

□□□□□□

1.5

1500mAh

□□□

□□□□	
□□	ABS + PVC + PC
□□	□ * □ * □□162□□ * 68□□ * 93□□
□□	169g±5g
□□	5V±5% 3.7v 1500mAh
□□□□	50MA; 30MA; 100MA
□□	□□□□□
□□□□	&100000
□□□□	
□□	USB; 2.4G
□□□□	Linux; Android; Windows XP; 7,8,10; MAC
□□□□	□□□□□□□□
□□	□□□□□□□□650nm
□□□	32 MCU
□□	64K 3500 14bit 1D
□□□□	□□200
□□□	4MIL
□□□□	70
□□□	5000000 1
□□□□	□□
□□□□	□□; □□□□
□□□□	□□□□□□□□LED
□□□□□□	35
□□□□	6-7
□□□□	□□24
□□	Code25-Interleaved Code25- Code25-Matri
□□	Code39- Code39-FullASCII Code32
	Code93- Code93-FullASCII Code128
□□□□	10-600
□□□□	Roll35°; Pitch65°; Yew65°
□□□□	Code39 5mil 3cm - 8cm
	Code39 10mil 4cm - 45cm
□□□□	
IP	IP52

□□□□	0□50°C/ 32□122°F
□□□□	0□50°C/ 32□122°F
□□□□	20□□85□□□□□□
□□□□	20□□85□□□□□□
ESD□□	15KV□□□□
□□□□	□□□□□1.5□□□□□