

□□□

200MM/S□□□□  
 10-60cm□□□  
 70m□□□2.4G□□□□  
 □□□□□□□  
 □□□□1.5m□□□□  
 1500mAh□□□□□

□□□

□□□	OCBS- W013
□□	□□, □□
□□	ABS+PVC+PC
□□□□□□	IP52
□□□	32□□□□
□□□□	>100000
□□	USB□□□□2.4G□□
□□□□□	□□□□□□□□□□
□□	5V ±5%□□□3.7v 1500mAh□□□□□
□□□□	50MA□□□□□□□30MA□□□□□□□ 100MA□□□□□□□
□□□□	□□□□□□□(LED)
□□□□	□□□□□□□□
□□	64K□□3500□14□□□□□□□□□□□□□□□
□□□□	□24□□
□□□□	6-7□□
ESD□□	15KV□□□□
□□□	□□□□□ 1.5m □□□□
□□□□	Linux□□□□Windows XP□7□8□10□MAC
□□	
□□	□□□□□□□□□□ 650nm
□□□□	200 □□□□/□
□□□□	10mm-600mm
□□□□□	35%
□□□	400□
□□□□	70m
□□□□	□□
□□□□	Roll35°;Pitch65°;Yew65°
□□□□	Code39 5mil:3cm - 8cm Code39 10mil:4cm - 45cm
□□□	1/5000000
□□□□	Code25-Interleaved Code25-Standard Code25-Matri x Code39-Regular Code39-FullASCII Code32 Code93-Regular Code93-FullASCII Code128
□□	
□□	□□□300□
□□	183 *1 18 * 85□□
20 □ 1 □	460 * 400 * 270□□/ 7.05□□
□□	
□□□□□□□	0□45□□□□10%~80%□□□
□□□□□□□	-20 □ 60 □□□□10%~90% □□□









