

2.4G 1D / 2D

OCBS -W217



□□

□□□□□□;

□□□□□;

4Mil □□□□□□;

2.4G □□□ USB □□□□

1200mah □□□□□□□□12□□

16MB □□□□□□□□100000□□□

□□□□□□□□□□;

□□□□□□1D□2D□□□□;

□□□□□□□□□□□□□□□□;

□□

□□	USB.
□□□□	Linux□Android□Windows XP□7,8,10□Mac
□□□	CMOS□□□□
□□	□□LED□□□□+□□LED□□□□
□□□	32□ARM MCU + DSP
□□□□	≥4mil□PCS90□□□□□39□
□□□	1/5□
□□□□	25cm / s.

□□□□	□□
□□□□	□□□□□□□□□□□□
□□□□	□□□□□□□□LED□
□□	2.4g□□
□□	1200mah.
□□	16MB.
□□□□	4□□□
□□□□	12□□
□□□□	≥25□
□□	ABS + PC.
□□	DC 5V±5□
□□	375MW□□□□; 226MW□□□□; 750MW□□□□
□□	□□□□□□
□□	289g±5g
□□□□	l * w * h□180 * 115 * 85□□□□mm□
□□□	60 * 45 * 38.5 cm 50 pcs / carton□nw□= 14.45kg□gw□= 16.15kg
□□	□□
□□□□	1D
	●Code25□□●Code25□□●Code25-Matri
	●Code39-Regular●Code39-Fullascii●Code32
	●Code93-Regular●Code93-Fullascii●Code128
	●EAN / GSL / UCC-128AUTO●CODABAR●MSI
	●EAN / JAN-13●UPC-A●JAN-8●UPCE
	2D
	●QR●□□□□●PDF417
□□□□	ROLL360°□□□30°□YAW45°
□□□□	Code39 4.17MIL□15□□□□□4cm - 8cm
	Code128 4.17MIL□16□□□□□7cm - 15cm
	□□□□10.83mil□8□□□□□3cm - 9cm
	□□QR 20mil□8□□□□□1cm - 19cm
□□□□	
IP□□	IP42.
□□□□	0□50°C/ 32□122‰
□□□□	0□50°C/ 32□122‰
□□□□	20□□85□□□□□□
□□□□	20□□85□□□□□□
ESD□□	15kV□□□□
□□□□	□□□1.5M□□□□□□□□□□