OCBS-W230:2D [[[[[[[

	95x65x155mm		
	ABS+PC		
	160g		

	617 nm LED				
	625 nm LED				
	39° (H) x 25° (V)			
	0 - 360°				
	± 65°				
	± 60°				
	□□□25%				
1D	UPC/EAN, UPC	C/EAN with supplem	nentals, BooklandEAN, ISSI	N, UCC Coupon	
	Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 FullASCII, Trioptic				
			l 1, Matrix 2 of 5, Interleave		
			SS1 DataBarvariants, Korea	-	
2D		· •	e Codes, TLC-39,Data Matr	ix, Maxicode, QR Code,	
	MicroQR, Aztec				
	USB□□				
	<u> </u> 100 300][]Max[]			
	-10° - 45°C				
	-20°C - 65°C				
	5%-85%				
	5%-95%				
	00001.8m				
	DC 5V∏350mA				
	□□3.000 LUX max□□□□□86000LUX max				
EMC	EN50081, par1 standard				
FCC	EN50082, par1 standard				
	IP42				
DECODE I	□□□□ DECODE RANGES				
Code 39		5.0 mil	5mm	90mm	
100% UPCA		13.0 mil	8mm	200mm	

Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39		2.8 mil (0.071mm)	
Resolution 2D Data Matrix		4.8 mil (0.122mm)	







Bookstore




Supermaket



Pharmacy



Warehouse





Restaurant

Parameter				
Physical Characteristics				
Dimension	95x65x155mm			
Material	ABS+PC			
Net Weight	160g			

- C	V	Optical Performa	nce	
Aiming Light Source	617 nn	n LED	WIN.	
Lighting Light Source	625 nm LED			
Scanning Angle	39° (H)	x 25° (V)		- , OV
Rotation Angle	0 - 360°			-0,00,
Elevation Angle	± 65°	W. J.	N)	1,
Tilt Angle	± 60°			
Print Contrast	Higher than 25%			
1D	Coupo FullASO Interle	n Extended Code, Code 12 CII, Trioptic Code 39, Cod	oplementals, BooklandEAN, IS 28, GS1-128, ISBT 128, Code 39 de 32, Code 93, Code11, Matr of 5, Codabar, MSI, Chinese 2 ISBT Concat	, Code 39 ix 2 of 5,
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode,			
	QR Co	QR Code, MicroQR, Aztec		
Interface	USB			
Communication distance	Inside:	100m; Outside: 300m ((Max)	
Operating Temperature	-10°C	-45℃	incol	
Storage Temperature	-20°C	-65°C	Min	00
Operating Humidity	5%-85	%		JW.
Storage Humidity	5%-95%			
Durability	Withstands multiple 1.8m drops to concrete			
Input Power	DC 5V, 350mA			
Lumination	Inside:	3.000 LUX max; Outs	ide sunlight: 86000LUX max	
EMC	EN50081, par1 standard			
FCC	EN500	82, par1 standard		
IP Grade	IP42			
		DECODE RANGE	ES	-67/4
Typical Performance*			Typical Working Ranges	
			HD Focus Range	
Bar Code Type		Symbol Density	Near	Far
Code 39		5.0 mil	5mm	90mm
100% UPCA	· Ohr	13.0 mil	8mm	200mm
Code 39	ν.	20.0 mil	8mm	250mm
PDF 417		6.8 mil	5mm	95mm
Data Matrix		10.0 mil	5mm	110mm
QR Code		20.0 mil	10mm	150mm
Resolution 1D Code 39		11/1/2	2.8 mil (0.071mm)	W
Resolution 2D Data Matrix		-61	4.8 mil (0.122mm)	



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist.

Test Equipment and Facilities

Verified	Qua	Brand & Model No.	Quantity
1	6	No Information	6
V	1	CC2670A	1
✓	1	TBS1102	1
1	6	PS-305DM	6
1	1	HP100	1
1	2	GUANGLU	2
1	7	VC890D	7
1	13	No Information	13
1		100000000000000000000000000000000000000	

Verified by TUV on 2013.7.15

Certification:









Warranty and After Sales:

- All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- Spare parts will be provided for mass orders for customers' local maintenance.
- Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.





















Payment:









secure payment







Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



Company Profile




TRADE ASSURANCE

- ■100% money refund for Late shipment&Quality problem
- Guarantee on-time delivery
- Third-party pre-shipment quality inspection (Optional)
- No transaction commission charged
- The HIGHEST assurance amount guaranteed by alibaba
- in the Auto-ID and POS industry .



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers, Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs. OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

















Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn; E-mail: ocom@ocominc.com, info@possolution.com.cn;

Tel: +86.755.86053207 ext 800; Fax: +86.755.86053207 ext 868; QQ: 2485890637, 190852203; Wechat: szocominc, hj34924238; Whatsapp: 008613352932860;



