



(OCBS-W230)

300x100mm
 95x65x155mm
 ABS+PC
 160g
 617 nm LED
 625 nm LED
 39° (H) x 25° (V)
 0 - 360°
 ± 65°
 ± 60°
 25%
 1D
 2D
 USB
 100x300mm Max
 -10° - 45°C
 -20°C - 65°C
 5%-85%
 5%-95%
 1.8m
 DC 5V 350mA
 3.000 LUX max 86000 LUX max
 EMC
 FCC
 IP42

	95x65x155mm
	ABS+PC
	160g

	617 nm LED
	625 nm LED
	39° (H) x 25° (V)
	0 - 360°
	± 65°
	± 60°
	25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 FullASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 DataBarvariants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, QR Code, MicroQR, Aztec
	USB
	100x300mm Max
	-10° - 45°C
	-20°C - 65°C
	5%-85%
	5%-95%
	1.8m
	DC 5V 350mA
	3.000 LUX max 86000 LUX max
EMC	EN50081, par1 standard
FCC	EN50082, par1 standard
	IP42

DECODE RANGES			
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39		2.8 mil (0.071mm)	
Resolution 2D Data Matrix		4.8 mil (0.122mm)	



