000433Mhz 00000 qr 02D 0000000

□□: ocbs-w231-4/b

□ :
$1 [433 Mhz \] [] [] [] [300 []] [] [100 m;] [] [] [] [20 m, \ 10 m \] [] [] [300 [] [300 []] [300 [$
200000000
3000000000, 00000000;
4000000000000;
5000000000;
600010000;
700000000000000000 (433mhz)0

|||:

	61700000		
	62500000		
	39 (h) x ° (v)		
	0-360 °		
	±65		
	±60°		
	□□25%		
1D	upc/supplementals, BooklandEAN, issn, ucc \(\bigcap_		
2D	PDF417, MicroPDF417, 🖂 🖂	, TLC-39,Data 🔲, 🛮, qr 🖟	MicroQR, 🖺 🗎 🗎
	usb (Wirelless 🖂 🖂 🗎		
	433mhz: □: 100m; □□: 300m (□□) □□: □: 10m; Outside:20m (□□)		
	-10 ° c-45 ° c		
	-20 ° c-65 ° c		
	5%-85%		
	5%-95%		
	1.5m		
	dc 5V, 280mA		
	6h		
	1500mAh		
lumination		00LUX [[[
ip □□	IP42		
0000 *			
□□39	5.0 🖂	5mm	90mm
100% upca	13.0 🖂	8mm	200mm

□□39	20.0 🛮 🔻	8mm	250mm	
pdf 417	6.8 🔲	5mm	95mm	
	10.0 🔲	5mm	110mm	
qr 🛮	20.0 🔲	10mm	150mm	
0001D 0039	4			
2D	10[[
	abs + pc			
	□□□ (70 * 95 * 168 mm) □□ (145 * 112 * 74 mm)			
	□□□185g □□186g			
	OCBS-W231-4: 433mhz 002d 0000000			
	OCBS-W231-B: [][][][] 2d barocde [][]			



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE











LONG DISTANCE WIRELESS COMMUNICATION

CHARGING CRADLE

NO NEED DRIVER, PLUG AND PLAY

STRONG DECODING ABILITY

STABLE STRUCTURE



FAST SCAN, HIGH RECOGNITION RATE





3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION





STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE





NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION, RICH TYPE OF DECODING

It'S APPLICATED AT ANY PLACE, THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT INORMATION

Aiming Light Source	617 nm LED		
Lighting Light Source	625 nm LED		
Scanning Angle	39° (H) x 25° (V)		
Rotation Angle	0 - 360°		
Elevation Angle	± 65°		
Tilt Angle	± 60°		
Print Contrast	Higherthan 25%		
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Barvariants, Korean 3 of 5, ISBT Concat		
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec		
Interface	USB (Wirelless receiver cable)		
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)		
Operating Temperature	-10 deg C - 45 deg C		
Storage Temperature	-20 deg C - 65 deg C		
Operating Humidity	5%-85%		
Storage Humidity	5%-95%		
Durability	With stands multiple 1.5m drops to concrete		
Input Power	DC 5V, 280mA		
Charging time	6h		
Battery	1500mAh		
Lumination	In side: 3.000 LUX max; Outside sunlight: 86000LUX max		
IP Grade	IP42		

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90 mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10 mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm)	Base(145*112*74mm)	
Net Weight	Scanner 185g Base 186g	1	
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

- Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- 2. EXPRESS: around 3-7 working days to arrive
- INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
- By sea: depend on which destination port
- 5. T/T
- Western Union
- 7. Escrow
- L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.













Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com Tel: 0086.755.86053207-815; Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: ocomsales15;

Whatsapp: +0086.189.4879.9080;