

2D CMOS

M / N OCBS -W233

□□□

- □□□+ 2.4G + USB□□
- 1□ □□□□□□□□□□
- 250□□□□□□□□ □□□□30,000□
- □□□□800□□□
- □□□□□□□
- □□long□□□□□□□□
- □□□□□□□□□□□□600□□□

□□	CMOS □5600K□□LED□
□□□	32□
□□□	1MP□1280 * 800□
□□□□	2.4G + USB□2.4G + Bluetooth + USB□□□□
□□□□□	2D□PDF417□Micro PDF 417□QR Code□QR1 / 2□Micro□□□□□□□□Aztec□□□□□□□□ 1D□UPC-A□UPC-E□EAN-8□EAN-13□Code128□Code39□Code 93□Code32□Code11□Codabar□Plessey□MSI□□□2□5□IATA 2□5□□□2□5□□2 □5□Pharmacode□RSS-14□RSS-14□□□RSS-14□□□Com pos□□-A□Com pos□□- B□Com pos□□-C□
□□□	□□≥400□□0.10□□□
□□□	2D≥700□□0.10□□□
□□□□	□39-5mil□60mm-120mm UPCA-13mil□100□□□35mm-310mm
□□□□□	□□1/8□□
□□□□□□□	≥ 30°
□□□□	□□□□□□55°□□□55°
□□	2000mAh□30000□□□□□□□□
□□□□	5VDC±10□
□□	□□□ 250mA±5□
□□□□	0°C□+ 50°C
□□□□	--40°C□+ 70°C
□□	5□-95□
□□□□	CE□IP54ROHS□FCC □EMC□□□□LVD
□□	275□
□□□□	190mm * 115mm * 85mm;
□□□□	50□/□; 16kg /□;
□□□□	600□□×450□□×420□□



OCBS-W233





OCBS-W233





OCBS-W233





OCBS-W233





OCBS-W233

