

OCBS-W234 Pos

(M/N:OCBS -W234 )

□□□

- 2.4GHz□□
- 80□
- 100□□□□□□□□□□
- 190mA□□□□□□□□40000□
- 12□□□□□
- 
- 1000 □□□

□□

□□□	OCBS - W234
□□	ABS+PC+TPU
□□□□□□	≥IP54
□□□□	2.4GHz
□□□□	□□□□□□□□□□□□
□□□□	□□□□□□□□LED □
□□	3.7V 2000mAH 18650 □□
□□□□	6.5□□
□□□□ □□	□12 □□
□□	□□ 5V ±5%
□□□□	190mA □□□□□□
□□□□	15KV
□□□	1.5M □□□□□□□□□□
□□	400□/□
□□□□	5 * 5 □□□□ -- 30 * 30 □□□□
□□	□□ LED □□ + □□ LED
□□□□	50-80M
□□□	1/5□
□□	2M □□40000□□□□□□□□□□
□□□	Code39 500 □□QR 870 □□PCS45%
□□□□□	□□ 35%
□□□□	Roll 0-360°, Pitch±65°, Yaw±60°
□□□□	Codabar,Code11,Code39/Code93,UPC/EAN,Code128/EAN128,InterLeaved2of5,Matrix2of5,MSI CODE,Standard2of5□ □□□□□□□□□PDF417 □Micro PDF 417
□□□□□□	5MIL CODE39□5--12 □□□ 15MIL CODE39□4--25 □□ 10MIL CODE93□4--21 CM □ 15MIL UPC/EAN□4--25 CM 20MIL QR : 4--25 CM
□□□	□□□500□
□□	210*130*95mm
20 □ 1 □	500 * 280 * 460□□/ 11.0□□
□□	
□□□□□□□	0□45□□□□10%~80%□□□□
□□□□□□□	-20 □ 60 □□□□10%~90% □□□