

1D/2D

OCBS-W288



1D2D

2.4G

	OCBS-W288
	+

材料	ABS+PC
功耗	待机功耗<195mA 工作功耗<130 mA
供电	3.3 VDC±/- 10%/500mA
接口	USB+2.4G/USB+2.4G+蓝牙
容量	1800mah
尺寸	12mm
重量	4g
显示	LED显示屏
频率	2.4G蓝牙
颜色	
分辨率	CMOS摄像头 640*480pixels/0.3MP摄像头
光源	LED灯
速度	蓝牙
精度	400μ
精度	±0.05mm
精度	1.2mm
精度	≥15°
精度	1D条码1D条码GS1 Databar™ 条码 2d条码maxicode;汉信; hanxin; MICROQR 条码GS1条码GS1条码GS1条码GS1条码MicroPDF417; PDF417
精度	1300mmEAN-13 55mm-380mm 1500mm128 45mm -480mm 500mm39 35mm-170mm 1500mmQR 25mm-340mm 1300mmEAN-13 55mm-380mm
精度	0-360°;±60°;Yaw±60°
精度	
精度	166mm
精度	160*64*86mm
精度	195*105*80mm/0.253kg
精度	560*410*430mm/14kg
精度	
精度	0°45°10°80°
精度	-20°60°10°90°















