

W299

- W299

1. 1. 2. 3. 4. 5. 6. 7. 8.

1. 1P
2. 1MP(1280*800)
3. ABSPC
4. 2.80
5. 130
6. 5 (-10%)/500mA
7. 1.2G
8. USB2.4G/USB2.4G

2. 3. 4. 5. 6. 7. 8.

1. 2. 3. 4. 5. 6. 7. 8.	- W299
1. 2. 3. 4. 5. 6. 7. 8.	ABSPC
1. 2. 3. 4. 5. 6. 7. 8.	2.80
1. 2. 3. 4. 5. 6. 7. 8.	130
1. 2. 3. 4. 5. 6. 7. 8.	5 (-10%)/500mA
1. 2. 3. 4. 5. 6. 7. 8.	1.2G
1. 2. 3. 4. 5. 6. 7. 8.	USB2.4G/USB2.4G
1. 2. 3. 4. 5. 6. 7. 8.	2000
1. 2. 3. 4. 5. 6. 7. 8.	LEd&
1. 2. 3. 4. 5. 6. 7. 8.	CMOS 1280*800
1. 2. 3. 4. 5. 6. 7. 8.	LED
1. 2. 3. 4. 5. 6. 7. 8.	G d
1. 2. 3. 4. 5. 6. 7. 8.	4
1. 2. 3. 4. 5. 6. 7. 8.	
1. 2. 3. 4. 5. 6. 7. 8.	8 KV
1. 2. 3. 4. 5. 6. 7. 8.	1.2 m
1. 2. 3. 4. 5. 6. 7. 8.	$\geq 1.5\%$
1. 2. 3. 4. 5. 6. 7. 8.	GS1 DataBar™ 2D GS1 DataBar Expanded Stacked GS1 DataBar GS1 DataBar PDF417 PDF417
1. 2. 3. 4. 5. 6. 7. 8.	334 39 60 m -160 334 EAN-13 90 -150 5 39 70 -240 5 EAN-13 70 -230 13 U A 40 -450 5 PDF417 65 -210 5 75 -140 1000 45 -290 1000 DM 30 -260 2000 20 -480
1. 2. 3. 4. 5. 6. 7. 8.	0-360° ±60° ±60°
1. 2. 3. 4. 5. 6. 7. 8.	3 00
1. 2. 3. 4. 5. 6. 7. 8.	1 72* 67* 87
1. 2. 3. 4. 5. 6. 7. 8.	1 75 *11 0 *8 0

20 1	4 2 0* 370 *2 37 / 7.0
	0 4 5 , 10%~80%
	-20 60 , 10%~90%











Acom 2D Barcode Scanner
Model: OCBS-W299
Interface: 2.4G&BT Color: Black
Power Input: 5V 0.5A

OCBSVZ992312300204 Made in China









