

# ATM

OCKP-8002

□□

160mm / s□□□□□

□□80□□□□□□

□□□□□

□□□□□□□□□□

□□□□□

□□NV□□□□□□

□□□□□□□□□□

□□□□□□100km

□□

□□□□	□□
□□□□	160□□/□
□□□□	Φ80□□
□□□	576□/□
□□	0.06□0.08□□
□□	USB + RS232
□□	GB18030□□□□□/□□□□□□□□
□□□□	ANK□□□A□1.5×3.0mm□12×24□□□□B□1.1×2.1mm□9×17□□
□□□□	UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□/ CODE39 / ITF / CODABAR / CODE93 / □□128 2D□QRCode / PDF417
□□□□□	32K□□
NV□□	64K□□
□□□□□	DC24V / 2.5A
□□□□□□	□□24V / 1A
□□	0.37□□
□□□□	132.2×125.7×88.11mm□□×□×□□
□□□□	□□□0□45□□□□10□80□□
□□□□	□□□-10□60°C□□□□10□80□□
□□□□□□	100□□



OCKP-8002





OCKP-8002





OCKP-8002







OCKP-8002







OCKP-8002





OCKP-8002





OCKP-8002

