

OCOM0000000058000000000000

OCPP-M06



OCPP-M06AndroidIOS + AndroidWindowLinuxJAVA58posUSBRS-232
8CEFCC

111

- [illegible]

111

□□□□□□×□×□□	105×75×45□□
□□	134□
□□	□□
□□□□	□□□□

功能	ESC / POS	
分辨率	48	
尺寸	90mm /	
点阵	8/203dpi	
打印范围	12x24 / 24x24	
打印速度	32/ 16	
打印头	1.5 x 3.0x/ 3.0x3.0x	
打印精度	58.0±0.1mm x40.0mm	
打印头间距	0.060.08mm	
接口	/	
接口	USB/RS-232	
容量	256KB	
电源	9V DC / 2A	
电池	7.4V DC / 1500mAh;4-5120-150m	
温度		
温度	-10~50°C10~90	
温度	-20~705~95	
温度	30ASCII	
温度	“ 1234”6	
温度	3.5 *1.1	
接口	OCP -M06-BB	AndroidUSB + COM +
	OCP -M06-BB-AI	Android + IOSUSB + COM +
	OCP -M06-B	AndroidUSB + COM +
	OCP -M06-U	AndroidUSB + COM
	OCP -M06-BB-AA	Android + IOSUSB + COM +7android +1

接口



```

##### Mini#####TAXI#####pos
t#####

```



