

0000 /0000 00 00000000

0000

0000 /0000 00

200 m h Z 32RSc

8 MB SDRM 8 MB

0000000000

1 52 m m 6 "00000000 00000000

300984 00 25.400000 m m1000000

203 DP300DP

00 00Rohm000000000000 100 00

00 000000 00000 0000000000 00000 00000000 00000 00000000

0000 bartender 00000000

00000000000000 00 0 00000 00 / 00 00000 / 00 / Mac - 000000

00

00	OCBP-t4202	OCBP-T4302
00	0000	
0000	32CPU	
00000	USB2.0 00000/USBBT/USBBTWFi/USBLAN	
0000 t IME c 0	00	
000000	TSPL	
000000000	10000	
00	I 00 0 AC 100V-240V 50-60Hz 00000 00 0 DC 24V / 2.5 A	
0000	00000000 00000000 00000 00000000 00000 00 00 0000	
00	8MB00/8MB SDRAM/00	
00	00000000 00000 USB00 00000 0000 00000 00000 0000000000 00000 00000X 21.50000000x 2 00000 00000x 200 00000	
00	000000Windows/Mac SDKWindows/Android/ios	
00000	0000 /00000	
00 i 0	8/000203 dpi	12 0/000 300 DPI
000000000000	1 52 00 0 6 "0/s	1 27 00 0 5 "0/s
000000000000	10 4 0004 09 "	104 0004 09 "
000000000000	1778 00 0 70 "	889 00 0 35 "
000000	bimap BMP PCX00025600000	

1D	3 9 9 3 1 2 8 U C C 1 2 8 a b c c o d a b a r 2 o f 5 E A N - 8 E A N - 1 3 E A N - 1 3 E A N - 1 2 8 E A N - 1 2 8 U P C - A U P C - E U P C - E E A N E A N U P C 2 5 M S I P O S T N E T P O S t G S 1 1 2 D P D F - 4 1 7 M i c r o c o d e D a t a M a t r i x Q R C o d e A Z T E C
8	alpha-numeric Windows
	0° 90° 180° 270°
	bimap BMP PCX 256
	20-112 0.78" -4.4"
	0.06 254 2.36 10 MIL
	10 1178 0 39 " 7 0 10 889 0 39 " 35
	127 5 OD
	300m M ax
	110
	25.4 1
	2 80 *2 10 *1 70 mm
	2.25 3.25kg
	370*240*205mm
4	500*390*430mm/14.5kg
	0 4 5 10 80
	-20 60 10 90

Thermal Transfer Label Printer

Versatility Creates Efficiency

- Thermal Direct Labels
- Thermal Transfer Labels
- PET Silver Labels
- Garment Hang Tags
- Wash Care Labels



Dual Printing Mode

Direct Thermal Print / Thermal Transfer Print

Switch at Ease Between Both Modes

Direct Thermal Mode

MODE 1



Direct
Thermal
Labels

No TTR Ribbons Required

Thermal Transfer Mode

MODE 2



Thermal Transfer Labels

PET Silver Labels

Garment Hang Tags

Wash Care Labels

TTR Ribbons Required

Professional and Durable Print Head

High-resolution Printing at Lightning Speeds

203dpi Printing Speed

152^{Max.}mm/s



Ordinary Print Head

Durability

Professional Print Head

Durability

Versatile Sizes Compatible Adjustable Media Guide

Different Sizes Printed by Guide Width Adjusted Flexibly



118mm
Media Width Max.

130mm
Media O.D. Max.

110mm×300m
Ribbon Size Max.

Widely Applicable Supporting Various Labels



Direct Thermal Labels



PET Silver Labels



Garment Hang Tags



Thermal Transfer Labels



Wash Care Labels



Price Tags



Various Connectivity

Multiple OS Compatible

Running smoothly with
Windows XP, 7, 8, 10, 11 and Mac OS

USB Connectivity

- ✓ Windows PC
- ✓ Mac

Also compatible with Google Chrome OS after installing the plugin in the Google browser.

Bluetooth Connectivity

For Bluetooth Version Only

- ✓ Windows Laptop
- ✓ Android Phone
- ✓ iPhone
- ✗ Mac

WiFi Connectivity

For WiFi Version Only

- ✓ Windows PC
- ✓ Mac
- ✓ Android Phone
- ✓ iPhone

Ethernet Connectivity

For Ethernet Version Only

- ✓ Windows PC
- ✓ Mac

Different Resolution for Option

For Different Printing Needs



For Most Printing Needs



For Fine Text Printing Needs

Resolution	203dpi	300dpi
Label Material	Direct Thermal Labels, Thermal Transfer Labels, PET Silver Labels, Synthetic PP Labels, Garment Hang Tags, Wash Care Labels	
TTR Ribbons	Wax Ribbon, Wax-resin Ribbons, Resin Ribbons, Washable Resin Ribbons	
Available Version	USB / Bluetooth / WiFi / Ethernet	
Media Type	Continuous paper, gap paper, folded paper, black mark paper, hole-punched paper	
Printer Dimension	280×220×168mm(L×W×H)	
Print Width	15-104mm	15-108mm
Print Speed	152mm/s	127mm/s

Default Accessories List



①



②



③



④



⑤



⑥



⑦



⑧



⑨

- ① User Guide ② USB Cable ③ Power Adapter ④ Power Cord
- ⑤ Media Shaft & Baffle Plate x 2 ⑥ Ribbon Shaft x 2
- ⑦ Ribbon Rewind Paper Core ⑧ Ribbon Sample Roll
- ⑨ Label Sample Roll