

OCOM OCPP-2012 USB

M / N OCBS -2012



□□□

- □□□□□□□□;
- □□□□□□□□□□;
- □□□□1D□2D□□□□□□□□;
- □□□□□□□□□□□□□□□□;
- 5mil□□□□□□□□□□□□□□□□;
- □□□□□□□□;
- □□□□□□;

□□□

□□□□	
□□□□	640 * 480,256□□
□□	LED□617 nm±10 nm□
□□	0~100,000 LUX
□□□□	□□360°\□□±60°\□□±65°
□□□□	300scan /□

□□	2D	DataMatrix□Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR□□Standard 2 of 5□Telepen□TLC 39□□
	1D	□□□□□□□Aztec□BPO□□□□□□□□Codabar□Codablock□Code 11□Code 39□Code 93□Code 128 / EAN128□Dutch Post□EAN.UCC Com pos ite□Interleaved 2 of 5□Japan Pos t□ Planet□Plessey Code□Pos tnet□RSS□UPC / EAN□□
□□□		≥5mil□□□□□□□□
□□		360°
□□		65°
□□		75°
□□□□		
□□		RS232 / USB / USB□□COM
□□		DC 5 V±5□
□□		190 mA□□□□
□□		1.5□
□□		165□
□□□□		170□□x 60□□x95□□
□□□□		
□□□□		-5°C□65°C
□□□□		-20°C□70°C
□□		5□ - 95□□□□□□
□□		□150□□□□□□□□

□□□□□



