

58

OCPP -58E

□□□

□□		□□
□□□□	□□□□	□□
	□□□□	48□□
	□□□□	384□/□□8□/□□□203dpi
	□□□□	90mm /□
	□□□□	USB□USB +□□
	□□□□	3.75□□□□□□□□□□□□□□
	□□	□□A□32 □□/□ □□B□42 □□/□ □□□□□□--16□
	□□	□□ GB18030 □□/□□□□ □□
	□□□□	□□□□□□A□1.5×3.0□□□12×24□□ □□B□1.1×2.1□□□9×17□□ □□□/□□□□□3.0×3.0□□□24×24 dOTS□
	□□□□□□	□□□□□□
□□		UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□CODE39 / ITF / □□/ CODE93 / CODE128
□□□□	□□□□	□□□□□□□□□□
□	□□	□□
	□□	57.5±0.5□□
	□□	≤60□□
	□□□□	□□□□□□
□□□□	□□	ESC/ POS
□□	□□□□□□	□□□□□□100V-240V□50--60□□ □□□□□□12V / 2A
	□□□□□□□□	□□12V / 1A
□□	□□□□□□	4K
	□□	40K
□□□□	□□	590□
	□□	185 * 130 * 112□□□□□
□□	□□□□	□□□5□45°C □□□10□80□
	□□	□□□-10□50°C □□□□10□90□□□□□□□□
□□□□□□	□□□□□□	50□□□□□□□□≤12.5□



OCPP-58E





OCPP-58E





OCPP-58E





OCPP-58E



Model: OCPP-58E
Print Speed: 100mm/s
Print Resolution: 203dpi
Print Density: 1200x1200
Current Codepage: 94
Support Character:
Simplified Chinese (GB18030)
Alphanumeric
CODE BAR:
1-UPC-A 2-UPC-E





OCPP-58E

