

OCPP -58E

111

□□		□□
□□□□	□□□□	□□
	□□□□	48□□
	□□□□	384□/□□8□/□□□203dpi□
	□□□□	90mm /□
	□□□□	USB□USB +□□
	□□□□	3.75□□□□□□□□□□□□□□
	□□	□□A□32 □□/□ □□B□42 □□/□ □□□□□□□--16□
	□□	□□ GB18030 □□/□□□□ □□
	□□□□	□□□□□□□A□1.5×3.0□□□12×24□□ □□B□1.1×2.1□□□9×17□□ □□□/□□□□□3.0×3.0□□□24×24 dOTS□
□□□□□□	□□□□□□	PC437 / □□□□/ PC850 / PC860 / PC863 / PC865 /□□/□□/□□□□□/ □□/□□/ WPC1252 / PC866 / PC852 / PC858 /□□□□/ □□□□□□□□/ PT151,1251 / PC737 / WPC / 1257 /□□□/ PC864 / PC1001 /□□□□□□□□□□PC1001□□□PT151,1251□□/ □□WPC1257□□□PC864□□□□□□□□□□□□
	□□	UPC-A / UPC-E / JAN13□□EAN13□□/ JAN8□□EAN8□□CODE39 / ITF / □□□/ CODE93 / CODE128
□□□□□	□□□□□	□□□□□□□□□□
□	□□	□□
	□□	57.5±0.5□□
	□□	≤60□□
	□□□□□	□□□□□□□□
□□□□□	□□	□□□/ POS
□□	□□□□□□	□□□□□□100V-240V□50--60□□ □□□□□□12V / 2A
	□□□□□□□□	□□12V / 1A
□□	□□□□□□	4K
	NV□□	40K
□□□□□	□□	590□
	□□	185 * 130 * 112□□□□□
□□	□□□□	□□□5□45°C□ □□□10□80□
	□□	□□□-10□50°C □□□□10□90□□□□□□□□□□
□□□□□□	□□□□□□	50□□□□□□□□□□≤12.5□



OCPP-58E





OCPP-58E







OCPP-58E



