

58mm Thermal Receipt

OCPP -58E

OCPP -58E

OCPP -58E

OCPP -58E

- OCPP -58E

- OCPP -58E

◆

- OCPP -58E;

◆

- OCPP -58E paperroll;

◆GB18030

- OCPP -58E uncommon characters

◆

- OCPP -58E;

◆

- OCPP -58E LOGO;

◆Linux Android IOS

- OCPP -58E Windows Linux Android IOS

Application Area

pos tal

OCPP -58E

OCPP -58E	OCPP -58E
OCPP -58E	OCPP -58E
OCPP -58E	48MM
OCPP -58E	384dots / 8dots / 203DPI
OCPP -58E	90/
OCPP -58E	USB USB +
OCPP -58E	3.75
OCPP -58E	A 32/ B 42/ 16
OCPP -58E	GB18030/
OCPP -58E	ANK character A. 1.5x3.0 12x24dots B. 1.1x2.1 9x17dots / 3.0x3.0mm 24x24

□□□□□	□□□□□	PC437 /□□□□/ PC850 / PC860 / PC863 / PC865 / WestEurope /□□/□□□□ □/□□□□□/□□/ WPC1252 / PC866 / PC852 / PC858 / IranII /□□□□□/□□□□□/ PT151,1251 / PC737 / WPC / 1257 / ThaiVietnam / PC864 / PC1001 /□□□□□□□□/□PC1001□□/□PT151,1251□□/□WPC1257□□/□PC864□□/ □□□□□/□□□□□
	□□	UPC-A / UPC-E / JAN13□EAN13□□/ JAN8□EAN8□CODE39 / ITF / CODABAR / CODE93 / CODE128
□□□□□	□□□□□	□□□□□□□□□□
□	□□	□□
	□□	57.5±0.5□□
	□□	≤60mm
	□□□□	□□□Clameshell□□□
□□□□	□□	ESC / POS
□□	□□□□□□	□□□AC 100V-240V□50-60Hz □□□DC 12V / 2A
	Casher□□□□□	DC 12V / 1A
□□	□□□□□	4K
	NV Flash	40K
□□□□	□□	590□
	□□	185 * 130 * 112□MM□
□□	□□	□□□5~45°C□ □□□10~80□
	□□	□□□-10~50°C □□□□10~90□□□□□□□□
□□□□□	□□□□□□	50KM□□□□□≤12.5□

□□□□□

□□□□□CD□□