

58

(M/N OCPP-58Y)



90

50mm

windows/Android/IOS

USB USBBT

nv

□□	
□□	OCPP-58Y
□□	58□□□□□□□□
□□	□□□
□□	USB/USB□□
□□	□□□AC 100V-240V,50-60Hz,□□□DC 12V/3A
□□□□□	50□□
□□	□□□□□ 64KB
□□□□□□	□□Windows/Android/IOS/Linux
□□□□	ESC□/POS
□□□□	
□□□□	□□□□
□□□	203 DPI□□□□□□□□
□□□□	90□□/□
□□□□	48□□
□□	3.75 mm□□□□□□□□□□
□□□□	□□□□/POS
□□□□□□	
□□	1D: UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□/ □□ 39 / ITF / CODABAR / □□ 93 / □□ 128
□□□□	384□/□□ANK□□□□□□□□A:1.5(W)*3.0(H) mm □□B□1.1□□□*2.1□□□mm □□/□□□3.0(W)*3.0(H)mm
□□□	PC347□□□□□□□/□□□ PC850□□□□□□□/PC860□□□□□□□ PC863□□□□□-□□□□/PC865□□□□□ □□/□□/□□□□/□□□□ WPC1252/PC866□□□□□□□#2□/PC852□□□□□□2□ PC858/□□□□/□□□□□□□□□□/PT151□1251□
□□	
□□□□	□□□□
□□□□	57.5±0.5□□
□□□□	□□50□□
□□□□	0.06-0.08□□
□□	
□□	115*100*120□□

□□	0.58□□
□□	
□□□□&□□	0□45°C□10%□80% □□□
□□□□□□□□	-20□60□□□□□10%~90%□□□











Version : 58.E-209-AA
Revised date: 28-Jun-2023
Command standard: EPSON(ESC/POS)
Print mode: Normal mode & Hex mode
Print method: Line thermal 384dots/line

acom



Version : 58.E-Z09-AA
Revised date: 28-Jun-2023
Command standard:EPSON(ESC/POS)
Print mode: Normal mode&
Hex mode
Print method: Line thermal
Print width: 384dots/line

 **Aocom**[®]
ESTABLISHED 2008



Version : 58 E-109-AA
Revised date: 28-Jun-2023
Command standard: EPSON (ESC/POS)
Print mode: Normal mode &
Hex mode







