

80MM

M / N OCPP -80F



□

□□□

1.300mm / s

2.2048K

3.□□1D□2D

4□

5□

6.□□□□□□□□□□□□□□□□

7.□□□□□□□□□80MM□58MM□□□□□ □□□□□

□□□□□□

□□	□□
□□□□	□□
□□□□	72□□
□□□□	576□/□□512□/□□8dots /□□□203DPI□
□□□□	□300mm /□
□□	□□□□100M□+ USB + COM;USB + COM
□□□□	3.75□□□□□□□□□□□□□□□□
□□	FontA-48Lines / FontB-64Lines /□□□□□□□□-24□
□□	□□GB18030□□/□□□□□□□□

□□□□	ANK□□□□A.□1.5×3.0□□12×24□□
	FontB□1.1×2.1□□9×17□□□□/□□□□3.0×3.0mm□24×24□□
□□□□□	PC437 /□□□/ PC850 / PC860 / PC863 / PC865 / WestEurope /□□/□□□□/ □□□□/□□/ WPC1252 / PC866 / PC852 / PC858 / IranII /□□□□/□□□□/ PT151,1251 / PC737 / WPC / 1257 / ThaiVietnam / PC864 / PC1001 /□□□□□□/□PC1001□/ □PT151,1251□/□WPC1257□/□PC864□/□□□□/□□□□
□□	1D□□□UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□CODE39 / ITF / CODABAR / CODE93 / CODE128
	□□□□□□□□
□□□□	□□□□□□□□
□□□□	□□
□□	□
□□	79.5±0.5□□
□□	≤80mm
□□□□	□□□Clameshell□□□
□□	ESC / POS
□□□□□	□□□AC 110V / 220V□50~60Hz
	□□□DC 24V / 2.5A
□□□□□□	DC 24V / 1A
□□□□□	2048K□□