

3 30000000 pos 000000

(M/N:OCPP-80F)



- 1.300mm/ 0000, 000000
- 2.2048K 00000000, 000000
- 3.Support 1 002000000
- 4. 000000000
- 5. 000000000, 000000;
- 6. 00000000000000
- 7.Movable 0000, 00 80 mm, 58 mm 0000

00000

00000:

00	00		
0000	000		
0000	72mm		
00	5760/5120 (8 000, 203 dpi)		
0000	3000/0		
00	000 (100 0) + usb + com;usb + com		
00	3.75mm (000000000)		
0 no0	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24 0		
00	00 GB18030 00/000000		
0000	0000, 00 a: 1.5x3.0mm (12x240)		
	FontB: 1.1x2.1mm (9x170) 00/0000: 3.0x3.0mm (24x240)		
00000	pc437/katakana/pc850/pc860/pc863/pc865/westeurope/greek/hebrew/easteurope/iran/wpc1252/pc866/pc852/pc858/irani/latvian/arabic/PT151,1251/PC737/00/1257/Thai/Vietnam/PC864/PC1001/(0000)/(PC1001)(PT151,1251)/(WPC1257)/(PC864)/(00)/(00)	00	1D 00: upc-a/upc-00JAN13 (EAN13)/JAN8 (EAN8) CODE39/00/codabar/code93/code128 2D 00: qrcode
0000	000000000		
0000	00		
00	0		
00	79.5±0.5mm		
00	≤80mm		
000	0000 (Clameshell 00)		
00	esc/pos		
00000	00: ac 110 0/220 0, 50 – 60 00 00: dc 24 v/2.5a		
000000	dc 24 v/1 a		
00000	2048K 00		
0000000	256K 00		
00	1.2KG		
0	186 * 145 * 135		
00	Temp:5~45 Centigrade, Humidity:10~80%		
00	Temp:-10 050000, 00:10 0 90% (Nodew)		
00000	10000 (0000) le. 12.5)		
00000	1000,000times		
00	android, ios, linux, Win2000, Win2003, winxp, Win7, Win8, win801		