

POS 58 80

M / N OCPP -80F



1.300mm / s

2.2048K

3.1D 2D

4.

5.;

6.

7.80MM 58MM

	72	
	576/512/8/ mm 203dpi	
	300mm /	
	100M + USB + COM / USB + COM	
	3.75mm	
	FontA-48Lines / FontB-64Lines / -24	
	GB18030 /	
	ANK 1.5x3.0mm 12x24	
	FontB 1.1x2.1mm 9x17 / 3.0x3.0mm 24x24	
	PC437 / PC850 / PC860 / PC863 / PC865 / WestEurope / / / / WPC1252 / PC866 / PC852 / PC858 / IranII / / / PT151,1251 / PC737 / WPC / 1257 / ThaiVietnam / PC864 / PC1001 / / / PC1001 / PT151,1251 / WPC1257 / PC864 / /	UPC-A / UPC-E / JAN13 / EAN13 / JAN8 / EAN8 / CODE39 / ITF / CODABAR / CODE93 / CODE128
		QR CODE
	79.5±0.5	
	≤80mm	
	Clamshell	
	ESC / POS	
	AC 110V / 220V 50~60Hz	
	DC 24V / 2.5A	
	DC 24V / 1A	
	2048K	
NV Flash	256K	
	1.2KG	
	186 * 145 * 135	
	5~45 10~80	
	10~50 10~90 Nodew	
	100KM LE.12.5	
	1000,000times	
	OS Linux Win2000 Win2003 WINXP Win7 Win8 Win8.1	