

IOS 3 pos WIFI

(M/N:OCPP-80F)

✖:

- 1.300mm/Printinghigh,
- 2.2048K,
- 3.Support12
- 4.
5. ,;
- 6
- 7.Movable, 80 mm, 58 mm

:

|    |  |
|----|--|
|    |  |
|    |  |
|    | 72mm   |
|    | 576/512 (8, 203 dpi)   |
|    | 300/   |
|    | (100) + usb + com;usb + com  |
|    | 3.75mm ( )   |
| no | fonta-48lines/fontb-64lines/simple,traditional Chinese-24  |
|    | GB18030 /  |
|    | , a: 1.5×3.0mm (12×24)<br>FontB: 1.1×2.1mm (9×17) /: 3.0×3.0mm (24×24)   |
|    | PC437/PC850/PC860/PC863/PC865/WestEurope//EastEurope/<br>/WPC1252/PC866/PC852/PC858/IranII//PT151,1251/PC737/<br>/1257/ThaiVietnam/PC864/PC1001/(<br>)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(/) |
|    | 1D : upc-a/upc-//JAN13 (EAN13)/JAN8 (EAN8) CODE39//<br>codabar/code93/code128  |
|    | 2D : qrcode  |
|    |  |
|    |  |

|         |  |
|---------|--|
| □□      | □  |
| □□      | 79.5±0.5mm   |
| □□      | ≤80mm  |
| □□□     | □□□□ (Clameshell □□)   |
| □□      | esc/pos  |
| □□□□□   | □□: ac 110 □/220 □, 50 ~ 60 □□                                   |
|         | □□: dc 24 v/2.5a   |
| □□□□□□  | dc 24 v/1 a  |
| □□□□□   | 2048K □□   |
| □□□□□□□ | 256K □□  |
| □□      | 1.2KG  |
| □       | 186 * 145 * 135  |
| □□      | Temp:5~45 Centigrade, Humidity:10~80%                            |
| □□      | Temp:-10 □50□□□, □□:10 □ 90% (Nodew)                             |
| □□□□□   | 100□□ (□□□□ le. 12.5)  |
| □□□□□   | 1000,000times  |
| □□      | android, ios, linux, Win2000, Win2003, winxp, Win7, Win8, win8□1 |