

80mm wifi

(M/N:OCPP-80F)

:

1. 300 /,

2.2048K,

3.Support12

4.

5. ;

6

7.Movable, 80 mm, 58 mm

.

:

|    |  |
|----|--|
|    |  |
|    |  |
|    | 72mm   |
|    | 576/512 (8 , 203 dpi)  |
|    | 300/   |
|    | (100 ) + usb + com;usb + com   |
|    | 3.75mm ( )   |
| no | fonta-48lines/fontb-64lines/simple,traditional Chinese-24  |
|    | GB18030 /  |
|    | a: 1.5×3.0mm (12×24)   |
|    | FontB: 1.1×2.1mm (9×17) : 3.0×3.0mm (24×24 )   |
|    | pc437/katakana/pc850/pc860/pc863/pc865/westeurope/greek/hebrew/easteurope/iran/wpc1252/pc866/pc852/pc858/iranii/latvian/arabic/pt151,1251/pc737/wpc/1257/ThaiVietnam/PC864/PC1001/(/)(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(/) |
|    | 1D : upc-a/upc-/JAN13 (EAN13)/JAN8 (EAN8) CODE39//codabar/code93/code128   |
|    | 2D : qrcode  |
|    |  |
|    |  |
|    |  |
|    | 79.5±0.5mm   |
|    | ≤80mm  |

|          |  |
|----------|--|
| □□□      | □□□□ (Clameshell □□)   |
| □□       | esc/pos  |
| □□□□□□   | □□: ac 110 □/220 □, 50 ~ 60 □□                                   |
|          | □□: dc 24 v/2.5a   |
| □□□□□□□  | dc 24 v/1 a  |
| □□□□□□   | 2048K □□   |
| □□□□□□□□ | 256K □□  |
| □□       | 1.2KG  |
| □        | 186 * 145 * 135  |
| □□       | Temp:5~45 Centigrade,Humidity:10~80%                             |
| □□       | Temp:-10 □50□□□, □□:10 □ 90% (Nodew)                             |
| □□□□□□   | 100□□ (□□□□ le. 12.5)  |
| □□□□□    | 1000,000times  |
| □□       | android, ios, linux, Win2000, Win2003, winxp, Win7, Win8, win8□1 |