

80mm OCPP-80G
M / N

Resolution	230dots/line 260dots/line
Print Speed	79.5±0.5dots/sec
Print Diameter	Φ80mm
Print Thickness	0.06-0.08mm
Print Density	576dots / line 512dots/line
Print Interval	3.75dots
Print Modes	ESC / POS
Print Interfaces	Parallel + USB + LAN / 36Pin / 25Pin + USB / LAN
CPU	100MHz
PRINT MEMORY	100Kbytes
RAM	2048Kbytes
NV MEMORY	256Kbytes
Power Input	AC110V / 240V 50/60HZ
Power Output	DC 24V / 2.5A
Power Consumption	DC 24V / 1A
Operating Temp.	0-45°C
Storage Temp.	0-45°C
Humidity	10-80%RH
Temperature	-10-60°C; Humidity 10-90%
Fonts	ANK FontA 1.5 * 3.0 / FontB 1.1 * 2.1
Barcode	UPC-A / UPC-E / JAN EAN13 / JAN8 EAN8 / CODE39 / ITF / CODE93 / CODE128 / PDF417
PC Interfaces	PC347 / PC850 / PC860 / PC863 / PC865 / WPC1252 / PC866 / PC852 / PC858 / IranII / PT151 / 1251
Dimensions	1.25mm; 190x145x143mm