

80MM 热敏 POS 打印机

OCPP -80H



特点

- 热敏打印
- 支持1D和2D条码
- USB + RS232 + LAN 3种接口
- 300mm / S 卷纸
- 100M 打印速度
- 256KB NV 内存 2M 闪存
- 支持热敏打印
- 支持 O POS 打印

规格

打印速度 300mm/分
厚度 79.5 ± 0.5 mm
打印直径 $\Phi 80$ mm
打印精度 0.06-0.08mm
分辨率 576dots / line 512点/行
Line 3.75mm
接口 ESC / POS
接口 USB + L
容量 > 1 mm
打印距离 100 km
内存 2048Kbytes

NV
Flash 256K

AC110V / 240V 50/60HZ

DC 24V / 2.5A

DC 24V / 1A

0~45 10~80N-

0~45 10~80N-

-10 60°C; Humidity 10 90

ANK FontA 1.5 * 3.0mm / FontB 1.1 * 2.1mm

UPC-A / UPC-E / JAN13 / JAN8 / EAN8 / CODE39 / ITF
/ CODE93 / CODE128 / PDF417

PC347 PC850 PC860 PC863 -
PC865 WPC1252 PC866 2
PC852 2
PC858 Iran PT151 1251



OCP-80H





OCPP-80H





OCPP-80H





OCPP-80H





OCPP-80H





OCPP-80H

