

80MM

OCPP-80K

8

100M

256KB NV Logo256kb

48mm80mm

O POS/JPOS

100KM

	ESC/POS
	576/512
	=72mm
	USB/UR/UL/URL/U+BT/U+WIFI/URL+BT/URL+WIFI
	200mm/s (U/UR) 230mm/s (UL) 260mm/s (U+BT/ U+WIFI/ URL/ URL+BT/ URL+WIFI)
	48mm/52mm/56mm/64mm/68mm/76mm/80mm
	0.06~0.08mm
	Ø 83
	256kbytes
NV	256kbytes
	A12*24B9*17
	GB18030,BIG5 24x24dots
	PC347(),PC850(),PC860(),PC863(-),PC865(), ,WPC1252,PC866(#2) ,PC852(Latin2), PC858,IranII, ,PT151(1251)
	UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
	USBUR
	100
	100V-240V 50/60HZ

電圧	24V/2.5A	
動作温度	0℃~45℃, 10%~80%RH	
保存温度	-10℃-60℃, 10%~90%RH	
付属品	CD-ROM (ドライバー、ソフトウェア)	
本体サイズ	196(D)x145(W)x135(H)mm	
重量	1.14 kg	
消費電力	1.5W	
本体サイズ (LxWxH)	30X19X18cm	10/10
本体サイズ (LxWxH)	62X36X52cm	12/10
対応OS	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS	
SDK	あり/あり	









Thermal Receipt Printer
Model: OCPP-80K
Interface: USB, RS232C, LAN
Paper Width: 80mm
Print Speed: 280mm/sec
Power Input: 24V/2.5A
Cash Drawer: 24V/1A
OCPP80K2137100139
Made in China
CE





