



OCPP-80K

80mm

USB/USB+Lan/USB+BT/USB+WIFI/URL+BT/USB+RS232

AC 100V-240V/50-60Hz DC 24V / 2.5 A

24V/1A

Max.20K

150

256KB NV Logo 256kb

48 80mm

150KM



OCPP-80K	OCPP-80K
80mm	80mm
USB/USB+Lan/USB+BT/USB+WIFI/URL+BT/USB+RS232	USB/USB+Lan/USB+BT/USB+WIFI/URL+BT/USB+RS232
AC 100V-240V/50-60Hz DC 24V / 2.5 A	AC 100V-240V/50-60Hz DC 24V / 2.5 A
24V/1A	24V/1A
Max.20K	Max.20K
150	150
256KB NV Logo 256kb	256KB NV Logo 256kb
48 80mm	48 80mm
150KM	150KM
UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/39/ITF/CODABAR/CODE93/CODE128	UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/39/ITF/CODABAR/CODE93/CODE128
GB18030	GB18030
384dots/line, ANK A: 12*24dots, 1.5(W)*3.0(H) mm	384dots/line, ANK A: 12*24dots, 1.5(W)*3.0(H) mm
B: 9*17dots, 1.1(W)*2.1(H)mm	B: 9*17dots, 1.1(W)*2.1(H)mm
U: 24*24dots, 3.0(W)*3.0(H)mm	U: 24*24dots, 3.0(W)*3.0(H)mm
PC437/PC850/PC860/PC863/PC865/WPC1252/PC866/PC852/PC858/ranl/PT151.1251/PC737/PC864/PC864/PC1001/(PT151.1251)/(WPC1257)/(PC864)	PC437/PC850/PC860/PC863/PC865/WPC1252/PC866/PC852/PC858/ranl/PT151.1251/PC737/PC864/PC864/PC1001/(PT151.1251)/(WPC1257)/(PC864)
48mm/52mm/56mm/64mm/68mm/76mm/80mm	48mm/52mm/56mm/64mm/68mm/76mm/80mm
0.06~0.08mm	0.06~0.08mm
83	83
196*145*135mm	196*145*135mm
1.65	1.65
300*190*180	300*190*180
12 1 1 615*370*535mm/21.5kg	12 1 1 615*370*535mm/21.5kg
0 to 45 °C, 10%~80%	0 to 45 °C, 10%~80%
-20 60 10%~90%	-20 60 10%~90%











