

80

OCPP -80P

1D QR PDF417

200mm / s

100

256KB NV 128KB

IAP

OPOS / JPOS

100

	ESC / POS
	576dots / line 512dots / line
	max = 72mm.
	USB / USB + LAN / URL / USB + / USB + WiFi / URL + / URL + WiFi
	200mm / s
	80
	0.06 0.08mm.
	83
	256kbytes.
NV Flash.	128kbytes.
	A 12 * 24 B 9 * 17
	GB18030 Big5 24x24dots
	PC347 PC850 PC860 PC863 PC865 WPC1252 PC866 2 pc852 2 PC858 PT151 1251
1D.	UPC-A / UPC-E / JAN13 EAN13 / JAN8 EAN8 / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D.	QR PDF417 USB
	100.
	AC 100V-240V 50 / 60Hz
	DC 24V / 2.5A
	0°C 45°C 10 80 RH
	-10°C -60°C 10 90 RH
	CD

□□	1□□
□□	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / OPOS / JPOS
SDK.	Android□□iOS.





OCPP-80P



**Attention:** Press FEED or re-start to reset cutter when it or cover stuck. If not, open here and turn the gear to reset cutter.





OCPP-80P





OCPP-80P





OCPP-80P







OCPP-80P





OCPP-80P

